

GPON FTTH ONT

i5850

Residential ONT

- The Icotera i5850 residential ONT integrates optical Ethernet-based gigabit data transmission with Layer 2-4 functionality, VoIP, 802.11ac & bgn Wi-Fi, CATV and USB 3.0.
- Best-in-class 4x4 Wave 2 MU-MIMO Wi-Fi
- Integrated ICONS remote monitoring solution
- Ease of use & installation
- OLT vendor independent
- Smart Home platform
- Award-winning industrial design



Powerful hardware platform

The Icotera i5850 fiber gateway demonstrates its great strength by bringing together a wide feature set and flawless performance. Its foundation is built on a powerful, cutting-edge dual-core architecture. This, paired with an ASIC for packet forwarding, ensures the platform is always ready to cope with additional tasks while processing VoIP, Gigabit routing of IPv4 with NAT, IPv6 and stateful filtering, traffic switching/bridging and high speed Wi-Fi.

Next generation Wi-Fi solution

With Wi-Fi becoming the preferred communication technology inside the home, the need for fast and stable wireless connections becomes ever more important. The i5850 delivers not only backwards compatibility with any 802.11a/b/g/n Wi-Fi certified device, but also includes the very latest standard – 802.11ac. With the added 802.11ac Wave 2 solution, the i5850 is capable of delivering 1700+300 Mbps and throughput which combined with MU-MIMO is able to deliver more than 1Gbps in real home and office environment.

Innovative feature set

The i5850 provides exceptional Layer 2 functionality that can effortlessly handle 16 bridging instances, 16 Wi-Fi APs over 2 radios, multiple WAN interfaces, PPPoE and in-band secure management. The CATV AGC receiver offers broadband cable-television services to the subscriber with seamless monitoring and configuration of the power levels. As an

optional feature, this fiber gateway offers a complete and customizable filter solution with low-pass filters for individual RF channel plans.

Ease of control

A great variety of management protocols (e.g. OMCI v2, SNMP v1/v2, syslog, SSH, Telnet and TR-069) is integrated and supported, which guarantees effortless control over the i5850. Paired with our fail-proof, zero-touch auto provisioning mechanism, they provide easy and trouble-free daily operations. To guarantee effortless firmware roll-outs, in harsh network environments, the i5850 also comes with dual-bank firmware.

Integrated Smart Home platform

The i5850 residential ONT supports 3rd party Smart Home platforms via state-of-the-art low-consuming wireless technology. A Smart Home platform offers great solutions for end-users within Alarm & Surveillance, Energy Management and Home automation. Via a cloud-based platform the i5850 connects to third party device-hardware, which makes the possibilities for connecting devices close to endless. For the network operator or service provider, a Smart Home platform offers a unique opportunity for additional revenue streams and higher customer loyalty.

i5850 Residential ONT

FEATURES

- Best-in-class Wi-Fi Wave 2 4x4 MU-MIMO solution
- OLT vendor-independent
- Award-winning industrial design
- Integrated CATV solution
- Low power consumption
- Optional operator branding
- Extensive IPv6 support
- Customized firmware
- Built-in Smart Home platform

NETWORK COMMUNICATION

GPON INTERFACE

- Single mode fiber (ITU-T G.652) SC/APC connector
- Data rate of 1.244Gbps/2.488Gbps (US/DS)
- Wavelength: TX 1310nm, RX 1490nm
- G.984.1,2,3,4,5 compliant
- Prepared co-existence for NG-PON
- OMCIv2 G.988 compliant
- Forward Error Correction (FEC)
- Ethernet GEM support
- Multiple T-CONTs/GEM ports per device
- AES encryption
- Dying Gasp
- Class B+ optics
 - Output level from +3 to +6dBm
 - Receiver sensitivity -30.5dBm

LAN INTERFACE

- 4x RJ45 connectors 10/100/1000 Base T(X)
- Auto-negotiation for speed and duplex
- Auto MDI/MDX
- Jumbo packets
- 802.1x
- Integrated cable tester, detects:
 - Short
 - Open
 - Impedance mismatch
 - Cable length

LAYER 2

- 16 bridge instances
- 64 byte forwarding at line rate
- Jumbo 9k packets
- IGMP v1/v2/v3 snooping
- 802.1p marking
- VLAN support
- Wi-Fi support
- Transparent IPv6 forwarding
- DHCP relay with option 82
- 2k address entries

Wi-Fi INTERFACES

802.11ac Wi-Fi

- 4x4 Wave 2 MU-MIMO
- 5 GHz band w/QAM256 and 80 MHz
- Authentication methods - Open - 802.1x - WEP64 - WEP128 - WPA - WPA2
- Up to 8 SSIDs
- MAC filtering
- Automatic channel selection
- Software Tx power control
- Extensive monitoring
- Neighbour scanning
- Beamforming
- LDPC + STBC
- Band steering

802.11bgn Wi-Fi

- 2T2R MIMO
- 2.4 GHz band w/QAM64 and 40 MHz
- Authentication methods - Open - 802.1x - WEP64 - WEP128 - WPA - WPA2
- Up to 8 SSIDs
- MAC filtering
- Automatic channel selection
- Software Tx power control
- Extensive monitoring
- Neighbour scanning
- Band steering

LAYER 3

- Virtual interfaces
- Multiple WAN interfaces in one router
- 64 byte forwarding at line rate with routing/NAT
- IGMP v1/v2/v3 proxy with fast-leave and monitoring
- Stateful Firewall
- IPv4 - SNAT, DNAT, DMZ - DNS proxy - DHCP client and server
- IPv6 - Prefix delegation RFC3769 - Auto configuration PPPoE (termination)
- 2k HW connection tracking
- SW connection tracking
- RTSP stateful proxy
- Protocol helpers for: SIP, FTP, TFTP

QoS

- 8 queues
- Layer 2 and 3 QoS features - Packet classification marking - Queuing - Scheduling - Rate-limiting
- Marking and Queuing w/ 802.1p, ToS, DiffServ classification
- Globally shared rate-limiting queues

USB

- 1x USB 2.0 host
- 1x USB 3.0 host

VoIP

- 2 separate POTS Lines SIP (RFC3261)
- 5 REN support
- DTMF signalling - SIP INFO - Inband - Auto - RFC 2833
- Caller ID support (DTMF/FSK/DTMF DK)
- CLIR
- Advanced dialplan
- B-Number manipulation
- Class 5 services - Forward all calls - Forward on busy - Forward on no answer - Call waiting
- Codecs: G.711A a-Law - G.711U μ -law - G.722 - G.729AB
- Modem/Fax detection
- Auto gain control
- Adaptive jitter buffer 10-300ms
- Silence suppression
- G.165 Echo Cancellation
- LEC (Line Echo Cancellation) 2- 128ms
- VAD (Voice Activity Detection)
- CNG (Comfort Noise Generation)
- PLC (Packet Loss Concealment)

CATV (OPTIONAL)

OPTICAL PARAMETERS

- Saturation power: +2dBm
- Input level range: -10 to 0 dBm
- Input wave length: 1550 nm
- Optical connector: SC/APC
- ITU-T G.652 Single Mode fiber
- Software monitoring of RX level in 0.1 dB steps
- Low-signal LED configurable

RF PARAMETERS

- RF connector: 75 Ohm "F"
- Frequency: 45-870MHz
- EIN @ -10dBm: 4 pA/ \sqrt Hz
- Tilt: 5 dB
- RF output AGC @ -8 to 0 dBm (3.5% OMI): 80 dBuV
- Max. RF output @ 0 dBm (3.5% OMI): 96 dBuV
- CNR (CENELEC 42 channels): \geq 51 dB
- CSO (CENELEC 42 channels): \geq 60 dBc
- CTB (CENELEC 42 channels): \geq 60 dBc
- RF filters (optional): up to 2
- Software adjustable RF output level w/ AGC

MANAGEMENT & MONITORING

- Shared or separate IP interface (VLAN or virtual) for management
- L1-L3 filters for all local services
- SSHv2 with key authentication
- Telnet with authentication
- End-user oriented web interface (configurable) - Wi-Fi - PPPoE - LAN network - Port forwarding, NAT loopback, DMZ, DynDNS, Status and monitoring
- TR-069 supporting - TR-104 (VoIP) - TR-181 (Network)
- CLI with auto-completion
- SNMP v1/v2 (IF-MIB, ICOTERA private MIB)
- Extensive debug possibilities
- Packet dumping
- All settings are stored locally in flash
- Zero-touch configuration with DHCP/TFTP or TR-069
- Automatic firmware and configuration update (polling)
- Dual bank firmware w/ fail-safe upgrading
- Wake-on-LAN for WebUI and CLI

OPERATIONAL SPECIFICATIONS

- DC12V input \pm 10%
- Power consumption maximum: 14.4 W (excl. USB ports)
- Operating temperature: 0 - 45°C
- Storage temperature: -20 - 85°C
- Humidity: 5% - 95% (non-condensing)

PHYSICAL SPECIFICATIONS


CASING

- Weight: 467 g
- Size: 233 x 162 x 41 mm (W x H x D)
- Front LEDs configurable by operator and/or end-user: - OLT link, Power/WAN status (link/traffic/provisioning) - VoIP port 1 - VoIP port 2 - Wi-Fi - CATV (status/signal power)
- LAN status LEDs (link/traffic, duplex) per interface
- LED auto off after timeout period

FIBER TERMINATION UNIT (OPTIONAL)

- Slide-on mechanism for easy installation
- FTU support for - Gas block unit (sold separately) - WDM filter (sold separately)
- Optional blind cover for FTU

i5850 Residential ONT Configuration possibilities



Gateway Interface Configurations:

Model	Uplink	LAN	USB	POTS	CATV	Wi-Fi	Antennas	Bottom
i5851-00	GPON	4x	2x	2x	1x	802.11b/g/n + 802.11ac	2x2 + 4x4 Int.	FTU/Patch
i5855-00	GPON	4x	2x	2x	-	802.11b/g/n + 802.11ac	2x2 + 4x4 Int.	FTU/Patch

NOTE: Please contact Sales for further details on information listed and feature requests.