

XGS-PON FTTH ONT

Baldur

Residential ONT for wholesale network operators

The Icotera Baldur optical network terminals (ONTs) integrate optical data transmission with Layer 2 functionality. The Baldur ONTs provide operators with advanced PON quality monitoring and allow them to flexibly implement wholesale solutions without compromising performance, creating a future-proof home setup.

- Designed for Open Access or wholesale deployment
- 10 Gbps multi-rate LAN port
- CWMP support for improved management and monitoring
- TR-143 for performance data and throughput statistics
- BBF.247 compliant
- OLT vendor-independent



Innovative features

The Icotera Baldur is an XGS-PON L2 termination device with full port flexibility, and multi-rate 10G, 2.5G, or 1G ports. In addition to OMCI, the ONT has an integrated CWMP stack that supports both IPv4 and IPv6 layers. This integration makes it possible to configure non-G.988 parameters such as LED indicators and EEE, monitor PON and LAN interfaces, and access such device information as CPU and memory usage, firmware version, and temperature. Also, the Baldur ONTs support network performance tests according to the TR-143 standard, which ensures that operators can validate endpoints beyond the OLT hence reducing the need for costly troubleshooting.

Built to last, designed for sustainability

The Baldur ONTs feature securely encrypted and signed firmware. It's designed to lower negative environmental impacts in the full life cycle:

Energy-Efficient Ethernet (EEE) reduces power consumption by up to 40% per LAN port. The high-quality components give the ONT an expected lifetime of over 10 years. Additionally, its housing is made of over 90% reused plastics.

Easy installation and integration

The Baldur ONT is BBF.247 compliant, ensuring interoperability with OLT devices from Nokia, Adtran, Huawei, and many others. Recognising the complexity of ONU and OLT integrations, the process is simplified by providing easy access to MIB data in standard JSON format. Also, a special integration software that mirrors all PON traffic for support and troubleshooting is available. Furthermore, a special integration software enables SSH access on the LAN port for remote troubleshooting.

The Baldur XGS-PON ONT has a variant with the fibre termination unit (FTU) that supports all types of fibre installation methodologies.



FTU installation (fX411-00)



Patch installation (fX310-00)

Baldur Residential ONT

FEATURES

- Vendor-independent ONT
- Hardware forwarding
- Protocol transparent forwarding

NETWORK COMMUNICATION PON INTERFACE

- Built-in WDM filter to support coexistence with CATV, GPON, and XGS-PON signals
- ITU-T G.9807.1 compliant
- Wavelength: US 1260 nm - 1280 nm, DS 1575 nm - 1580 nm
- 10 Gbps symmetric line rate
- G.984.1,2,3,5 compliant
- G.988 compliant
- Forward Error Correction (FEC)
- AES encryption
- Dying gasp
- Class N1 optics

LAN INTERFACES

- 2x or 1x 10/5/2.5/1 Gbps multi-rate Ethernet ports
- Up to 3x 1 Gbps Ethernet ports (optional)
- Auto-negotiation for speed and duplex
- Energy-Efficient Ethernet (EEE) control

LAYER 2

- 64 byte forwarding at line rate
- Jumbo 9k packets
- Forwarding up to 256 MAC addresses
- VLAN QinQ support
- VLAN 802.1ad support
- Transparent IPv6 forwarding
- Multicast support

LAYER 3

- Virtual WAN interface configurable through an IP host (OMCI)
- Support for IPv4
- Support for IPv6
- Support for static IPv4

QoS

- Support DBA in SR and NSR modes
- Support for Strict Priority and Weighted Fair Queuing
- Support up to 20 T-CONTs
- 8 upstream queues configurable via OMCI
- 8 downstream queues per LAN port configurable via OMCI
- Class of service based on VLAN-ID, 802.1p
- Marking and remarking of 802.1p
- Marking and remarking of DSCP/ToS

MANAGEMENT & MONITORING

- Zero-touch configuration with OMCI provisioning
- CWMP (TR-069) for monitoring and provisioning
- Dual bank flash memory with fail-safe firmware upgrading
- Hardware watchdog
- TR-143 for performance data and throughput statistics
- iPerf for throughput testing
- SSH client for a configured virtual WAN interface

OPERATIONAL SPECIFICATIONS

- DC 12 V input
- Operating temperature: 5°C - 45°C
- Storage temperature: 5°C - 85°C
- Humidity: 5% - 95% (non-condensing)

PHYSICAL SPECIFICATIONS

CASING

- Size: 135 x 135 x 30 mm (W x H x D)
- Product SN, PON SN, FW version and MAC address label on the bottom side
- PON LED indicator for the connection status
- LED indicators on LAN ports for the link status

FIBRE TERMINATIONS

- Slide-on mechanism for easy installation
- Patch variant for wall or tabletop installations

INCLUDED IN THE BOX

- Icotera Baldur ONT
- 12 V power supply unit
- Fibre termination unit (FTU) with a screw for secure locking
- 2 labels with the PON serial number

ESG and SUSTAINABILITY

Product data aligns with the European Sustainability Reporting Standards (ESRS).

Icotera CO₂ reduction targets are approved by the Science Based Target initiative (SBTi).



DRIVING AMBITIOUS CORPORATE CLIMATE ACTION

By 2030, Icotera will reduce the scope 1 and 2 greenhouse gas (GHG) emissions by 42%.

Climate (ESRS E1)

- Product CO₂ footprint (cradle-to-gate) data is available on request

Pollution (ESRS E2)

- Less than 0.1% hazardous substances in raw materials
- No flame retardants or plastic softeners in plastic parts
- Halogen-free printed circuit boards
- Available in up to 90% post-consumer recycled (PCR) materials
- Packaging: plastic-free, PE bag-free, 95% recycled cardboard
- Compliance with RoHS and the Swedish chemical tax rate for electrical equipment

Social (ESRS S2)

- Suppliers comply with the Icotera Supplier Code of Conduct: <https://bit.ly/icotera-code>

Distribution (ESRS E1)

- The CO₂ data on logistic solutions (ESRS E1) is available on request

Use

- Power consumption complies with the European Ecodesign Directive 2009/125/EC
- Energy-Efficient Ethernet support reduces power consumption by up to 40% per LAN port

End of life (ESRS E5)

- Built with high-quality components for 10 years expected lifetime
- Disassemblable for recycling
- WEEE producer and packaging responsibility is handled through Elretur and Emballageretur

Icotera Baldur residential ONT configuration options



Interface configurations

Model	Uplink	10G LAN port	1G LAN port	Installation
fx310-00	XGS-PON	1x	N/A	Patch
fx311-00	XGS-PON	1x	N/A	FTU
fx410-00	XGS-PON	1x	3x	Patch
fx411-00	XGS-PON	1x	3x	FTU
fx710-00	XGS-PON	2x	N/A	Patch
fx711-00	XGS-PON	2x	N/A	FTU

For more information and feature requests, contact our Sales department at sales@icotera.com.